Contents

1 Scope 7
1.1 General 7
1.2 Wireless vs. wired backhaul networks 7
1.3 Specific goals 8
2 Normative references 8
3 Terms, definitions and abbreviations 9
3.1 Terms and definitions 9
3.2 Abbreviations 17
4 Backhaul architecture 19
4.1 General 19
4.2 Backhaul model 19
4.3 Architecture elements 20
4.4 Interface model 21
4.5 Interface definitions 21
5 Security model 22
5.1 Overlay of IEC 62443 on this architectural model 22
5.2 Per-interface security description 24
5.3 System policies 26
5.4 Identity and authentication 26
5.5 Status and event logging 27
6 Distributed management model 27
6.1 General 27
6.2 Functions of the “configuration, security and management domain (CSMD)” 27
6.3 Management communication channels 27
6.4 Distributed management security 28
6.5 Event logging 29
6.6 Common configuration sets 29
6.7 Management protocols 29
6.8 Bootstrapping challenges 29
7 Fault tolerance model 29
7.1 General 29
7.2 Redundant backhaul networks 29
7.3 Redundant backhaul interfaces 30
7.4 Redundant links 31
7.5 Fault detection, notification and handling actions (auto/manual) 31
7.6 Online maintenance and upgrades 31
8 Mobility model (for example, mobile workers) 32
8.1 General 32
8.2 Mobile workers in different zones 32
8.3 Multi-access-point mobility for a given user 33
9 Flow control model 34

9.1 Overview 34
9.2 Functions of flow control 35
9.3 Per-interface flow control functions 39
9.4 Flow control policies 40
9.5 Flow control model for mobility 41
9.6 Flow control model for security 41
Annex A (informative) – Example implementation using the Purdue reference model 43
BIBLIOGRAPHY 44

Figure 1 — Example applications using a shared backhaul network 7
Figure 2 — Example industrial control system using backhaul connectivity 19
Figure 3 — Generalized backhaul interface model 20
Figure 4 — Example showing mapping of backhaul interfaces to IEC 62443 security model 23
Figure 5 — Example of remote management capability 28
Figure 6 — Redundant BSPs and multi-homed BHIs 30
Figure 7 — Redundant BHIs and redundant links 31
Figure 8 — Example of mobile workers in different zones 32
Figure 9 — Example of a single mobile worker migrating between access points in a given zone 33
Figure 10 — Flow control example for backhaul 34
Figure 11 — Example of flow control with third-party BSP 36
Figure 12 — Examples of edge router locations 38
Figure 13 — Example using backhaul architecture model and extended Purdue reference model 43