


SP06PC - Pre-Instructional Survey

Name _____ Date _____

1. What valve size is the most common in a facility?
 - a. 2 inch
 - b. <1 inch
 - c. >6 inch
 - d. 1 inch

2. The monitoring instrument shall be equipped with a probe not to exceed _____ in outside diameter?
 - a. 1/2"
 - b. 1/4"
 - c. 1"
 - d. Can be as large as needed

3. On a typical P&ID this symbol indicates which of the following 
 - a. check valve
 - b. gate valve
 - c. control valve
 - d. pump

4. A monitoring instrument does not have to be calibrated if you're only checking one component.
 - a. True
 - b. False

5. The more rings of packing in a valve give you a better chance of stopping a leak?
 - a. True
 - b. False

6. When does a precision calibration have to be done on an instrument?
 - a. Once every quarter
 - b. Prior to place the instrument into service
 - c. When repairs have been made that would change the response time
 - d. All of the above

7. Response time is the time between removing the zero gas and to when _____ of the calibration gas is attained?
 - a. 95%
 - b. 80%
 - c. 90%
 - d. 100%

8. Valve stem finish on a valve is usually checked during the repacking of a valve?
 - a. True
 - b. False

9. When being audited by a state or federal agency it is important to answer every question without hesitation?
 - a. True
 - b. False

10. Putting two valves back to back (or piggy back) will assure that you will not have an open end line?
 - a. True
 - b. False

SP06PC - Pre-Instructional Survey Answer Sheet

1. b
2. b
3. a
4. b
5. b
6. d
7. c
8. b
9. b
10. b